

Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.

## A-PAK - ALARM SYSTEMS

### INDOOR/OUTDOOR ALARM SYSTEM FEATURES

- Indoor & Outdoor use per UL 864.
- UL Listed and CSA Certified.
- Alarm system (horn & light) operates to warn of a high water condition.
- Horn is rated 82 decibels at 10'.
- Alarm Test and Horn Silence Switch with auto reset.
- Terminal connections for a pump & float switch.

#### Standard Model (P/N 10-0623) Includes:

- 15 ft. float switch.

#### Deluxe Model (P/N 10-0682) Includes:

- 20 ft. float switch.
- 6 ft. power cord plugs into 115V outlet.
- Watertight cord connectors.

### “A-PAK” ALARM SYSTEM FEATURES

#### 10-1494 (115V/1Ph/9V DC)

- Auto reset solid state alarm.
- 9 Volt battery back-up (battery not included).
- NEMA 1 non-corrosive enclosure for indoor use.
- Manual shut off.
- Float operates on 12 VAC.
- Float switch with 15' cable included.
- 6 ft. power cord plugs into 115V outlet.
- Horn is rated at 86 decibels at 10'.

### “A-PAK II” ALARM SYSTEM FEATURES

#### 10-0126 (115V/1Ph)

- NEMA 4X thermoplastic alarm panel.
- Horn & light warn of high liquid levels
- Test and silence switch.
- Auxiliary dry high level alarm contacts - 5 amps.
- Operates on separate circuit from pump 115 VAC.
- UL Listed for US & Canada.
- Float switch with 15 ft. cable included.
- Can be used with liquids to 140°F (60°C).
- Horn is rated at 88 decibels at 10'.

#### 10-0015 (115V) / 10-0016 (230V)

- Non-enclosed model.
- 6" magnetic bell with transformer.
- Mount on standard utility box (not included).
- Operates with 10-0743 float switch or mechanical alternator (not included).

Note: All variable level float switches in this section are mechanically activated and do not contain mercury.



